

Mobile Paint Mfg. Co., Inc.
MATERIAL SAFETY DATA SHEET

Product Name: WEATHER PROTECTOR IINTERIOR/EXTERIOR Acrylic Latex Stain

Product Code: 1412-10, 1412-40

SECTION V – REACTIVITY DATA

STABILITY: Stable

INCOMPATIBILITY (MATERIALS TO AVOID): None

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: By fire may produce carbon monoxide, carbon dioxide.

CONDITIONS TO AVOID: Fire, extremely high temperatures

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION VI – HEALTH HAZARD DATA

PRIMARY ROUTE(S) OF ENTRY: Inhalation, skin contact, eye contact, ingestion.

EFFECTS OF OVEREXPOSURE - ACUTE:

Dizziness, headache, nausea, confusion, irritation to upper respiratory tract (nose, throat), skin and eye irritation.

EFFECTS OF OVEREXPOSURE - CHRONIC:

None Known

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

None expected when used in accordance with Safe Handling and Use information (Section VII). May provoke asthmatic response in persons with asthma who are sensitive to airway irritants.

EMERGENCY AND FIRST AID PROCEDURES:

Inhalation: Remove to fresh air. Consult physician if there is difficulty in breathing. Skin: Wash affected areas with soap and water. Remove and launder contaminated clothing. Consult a physician if needed. Eyes: Flush immediately with large amounts of water for at least 15 minutes. Take to a physician for medical treatment. Ingestion: Drink 1 or 2 glasses of water to dilute. Do not induce vomiting. Consult a physician or Poison Control Center.

SECTION VII – PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Floors may be slippery, use care to avoid falls. Contain and remove with inert absorbent, transfer to container for disposal. Keep spill out of municipal sewers and open bodies of water.

WASTE DISPOSAL METHOD:

Dispose of in accordance with local, state and federal regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Do not store above 120 F. Store large quantities only in buildings designed to comply with OSHA 1910.106. Keep closures tight and container upright to prevent leakage. Never use pressure to empty. Drum must not be washed out or used for other purposes. Use with adequate ventilation. Avoid contact with skin and clothing.

OTHER PRECAUTIONS:

Do not get in eyes. Avoid skin contact. Wash contaminated clothing thoroughly. Wash skin thoroughly with soap and water after handling. Close container after each use. Do not transfer this product to unlabeled containers. Do not handle until the manufacturer's safety precautions have been read and understood. Keep out of reach of children.

SECTION VIII – CONTROL MEASURES

RESPIRATORY PROTECTION:

Use NIOSH approved respirator specified for protection against paint spray mist and sanding dust during spray application or sanding of dried paint.

VENTILATION:

Provide ventilation in volume and pattern to keep TLV and LEL below acceptable limits (see Sections II and IV). Open windows and doors to keep paint odor at minimum. Mechanical exhaust (fan) may be required in confined areas. These coatings may contain materials classified as nuisance particulates which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section II, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m³ (total dust), OSHA PEL 15 m g/m³ (total dust), 5 mg/m³ (respirable fraction).

PROTECTIVE GLOVES:

Use gloves impervious to water and soap.

EYE PROTECTION:

Safety eyewear including splashguards or side shields recommended.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

Use protective outerwear and prevent prolonged skin contact with contaminated clothing.

WORK/HYGIENIC PRACTICES:

Avoid breathing vapors and contact with skin. Wash skin thoroughly before breaks and meals and at end of work period.

SECTION IX – DISCLAIMER

DISCLAIMER: The information provided in this MSDS has been obtained from sources believed to be accurate and reliable. It is furnished without warranty of any kind, express or implied. Recipients should determine that the information is current and suitable for the protection of the environment and the health and safety of your employees and users of this product.