



# Mobile Paint Mfg. Co., Inc.

## MATERIAL SAFETY DATA SHEET

Product Name: Vinyl Wash Primer

Product Code: 9-48A

### SECTION V – REACTIVITY DATA

STABILITY: Stable

INCOMPATIBILITY (MATERIALS TO AVOID): Oxidizing materials

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Carbon monoxide, aldehydes and acids and other organic compounds may be formed during combustion.

CONDITIONS TO AVOID: Heat, sparks, flame and other possible ignition sources.

HAZARDOUS POLYMERIZATION: Will not occur.

### SECTION VI – HEALTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

Early moderate central nervous system depression as evidenced by giddiness, headache, dizziness and nausea. In extreme cases, unconsciousness and death may occur.

INGESTION HEALTH RISKS &amp; SYMPTOMS OF EXPOSURE:

Can cause gastrointestinal irritation, vomiting, nausea, and diarrhea.

SKIN &amp; EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

Skin: Can dry and defat skin causing cracks, irritations and dermatitis. Eyes: Can cause severe irritation, redness, tearing, blurred vision.

EFFECTS OF OVEREXPOSURE:

Inhalation: dizziness, breathing difficulty, headaches, loss of coordination.

Eye Contact: sever irritation, tearing, redness, and blurred vision.

Skin Contact: can dry and defat skin causing cracks, irritation, and dermatitis.

Ingestion: Can cause gastrointestinal irritation, vomiting, nausea, and diarrhea.

CARCINOGENICITY:

NTP? No IARC MONOGRAPHS? No OSHA REGULATED? Yes

Chromium and certain forms of Chromium compound are listed as carcinogen by NTP, IARC and ACGIH

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

Allergy, eczema, asthma, other skin conditions.

EMERGENCY AND FIRST AID PROCEDURES:

Skin: Wash affected areas with soap and water. Remove and launder contaminated clothing. Consult a physician if needed. Eyes: flush immediately with large amounts of water for at least 15 minutes. Take to a physician for medical treatment. Ingestion: Drink 1 or 2 glasses of water to dilute. Do not induce vomiting. Get medical help immediately. Inhalation: Remove to fresh air. If not breathing, give mouth-to-mouth resuscitation. If breathing is difficult, give oxygen. Call a physician.

### SECTION VII – PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Remove all sources of ignition (flame, hot surfaces, and electrical, static or frictional sparks). Avoid breathing vapors. Ventilate area. Contain and remove with inert absorbent and non-sparking tools. Thoroughly flush contaminated area with water.

WASTE DISPOSAL METHOD:

Dispose of in accordance with local, state and federal regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Keep away from heat, sparks and open flame. Avoid contact with eyes, skin and clothing. Avoid breathing vapor, mist or spray. Use only with good ventilation. Wash after handling. Store in closed containers in cool, well ventilated area.

OTHER PRECAUTIONS:

Do not get in eyes. Avoid skin contact. Can cause allergic respiratory reaction. Can cause allergic skin reaction. Prevent prolonged or repeated breathing of vapors or spray mist. Avoid breathing of sanding dust. Wash contaminated clothing thoroughly. Wash skin thoroughly with soap and water after handling. Close container after each use. Do not transfer this product to unlabeled containers. Do not handle until the manufacturer's safety precautions have been read and understood. Keep out of reach of children.

### SECTION VIII – CONTROL MEASURES

RESPIRATORY PROTECTION:

Atmospheric concentrations should be maintained below the threshold limit guidelines provided. When these concentrations cannot be maintained, respiratory protection is required. Use NIOSH/MSA approved chemical/mechanical filters designed to remove a combination of particulate, gaseous and vapor materials. In confined areas, use a NIOSH/MSA approved positive-pressure, self-contained breathing apparatus. Wear respiratory protection such as NIOSH/MSHA TC 21D-132 dust/mist respirator when sanding, grinding, blasting or cutting the dry film of this material.

VENTILATION:

Where possible, provide general and/or local exhaust ventilation to control airborne levels below the threshold limit values.

SKIN PROTECTION:

For brief contact, no precautions other than clean body-covering clothing should be needed. Use impervious gloves when prolonged or frequently repeated contact might occur.

EYE PROTECTION:

Use splash proof chemical goggles or safety eyewear including side shields recommended.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

Use impermeable clothing, aprons and protective covering whenever possible to prevent skin contact. Wear head covering whenever possible.

WORK/HYGIENIC PRACTICES:

Avoid breathing vapors and contact with skin. Wash skin thoroughly before breaks and meals and at end of work period.

### SECTION IX – DISCLAIMER

**DISCLAIMER:** The information provided in this MSDS has been obtained from sources believed to be accurate and reliable. It is furnished without warranty of any kind, express or implied. Recipients should determine that the information is current and suitable for the protection of the environment and the health and safety of your employees and users of this product.